

SYM5447THB 560C-8A TRUCK-MOUNTED CONCRETE PUMP

Energy-saving

Pump efficiency is increased up to 25% while fuel consumption is decreased by up to 10%.

Safety

Our truck mounted concrete pump exemplifies Sany's precise, rigorous manufacturing philosophy and uncompromising focus on safety.

Highly Wear Resistant Parts

The highly wear resistant parts improve efficiency and reduce down time.

Self-diagnosis Technology

Continually monitors more than 200 aspects of the system during operation. Faults are displayed on the monitor. Review of the detected faults can reduce troubleshooting time by 70%.

SANY HEAVY INDUSTRY CO., LTD.



TECHNICAL SPECIFICATION

Model			SYM5447THB 560C-8A
c			13950
Overall	Width(mm)		2550
Overall ecificati	Height(mm)		4000
Spe	Dead Weight(kg)		44000
	Vertical Reach(m)		56
	Horizontal Reach(m)		51
	Reach Depth(m)		36.6
	Unfolding Reach(m)		15.2
	1st Section	Length(mm)	11390
uo		Articulation(°)	89
Boom & Outrigger Specification	2nd Section	Length(mm)	9230
CCIE		Articulation(°)	180
Spe	3rd Section	Length(mm)	8750
ger		Articulation(°)	180
ıtrig	4th Section	Length(mm)	11070
O X		Articulation(°)	240
E .	5th Section	Length(mm)	8080
Воо		Articulation(°)	210
	6th Section	Length(mm)	3350
		Articulation(°)	110°
	Rotation(°)		±360
	Front Outrigger Spread L-R(mm)		9470
	Rear Outrigger Spread L-R(mm)		12680
	Output (m³/h)	Low-Pressure	180
		High-Pressure	125
	Pressure (MPa)	Low-Pressure	8.3
E O		High-Pressure	12
cati	Max. strokes	Low-Pressure	29
i <u>i</u>	per minute (times/min)	High-Pressure	19
Pumping Systerm Specification	Delivery Cylinder Diameter(mm)		260
Brm _	Stroke Length(mm)		2100
yst	Hydraulic System		Open
S gr	Hydraulic System Oil Pressure(MPa)		32
n jidu	Oil Tank Capacity(L)		680
Pur	Water Tank Capacity(L)		620
	Pipe Diameter(mm)		125
	End Hose Length(m)		3
	End Hose Diameter(mm)		125
	Chassis Brand		ISUZU
ion	Chassis Model		QL5440TZZW2VDHY
icat	Engine Type		6WG1-TCG51
ecil	Engine Maximum Net Power(kW/rpm)		337kW/1800rpm
Chassis Specification	Emission Standard		China V
ISSI	Fuel Tank Capacity(L)		600
Cha	Displacement(L)		15.681
	Max. Speed(km/h)		100